

ЗАКАЗАТЬ: 5АИ электродвигатели общепромышленные

Тип электродвигателя	Число полюсов	Габаритные размеры, мм				Установочные и присоединительные размеры, мм																		
		I30	I33	h31	d24	l1	l2	l10	I31	d1	d2	d10	d20	d22	d25	b1	b2	b10	h1	h2	h5	h6	h10	h
5А 200 L	2	805	920	475	450	110	110	305	133	55	55	19	400	19	350	16	16	318	10	10	59	59	25	200
5А 200 L	4; 6; 8	835	950	475	450	140	110	305	133	60	55	19	400	19	350	18	16	318	11	10	64	59	25	200
5АИ 200 L	2	770		510	450	110		305	133	55		19	400	19	350	16		318	10		59		25	200
5АИ 200 L	4; 6; 8	800		510	450	140		305	133	60		19	400	19	350	18		318	11		64		25	200
5А 225 M	2	835	952	535	550	110	110	311	149	55	55	19	500	19	450	16	16	356	10	10	59	59	30	225
5А 225 M	4	865	1012	535	550	140	140	311	149	65	60	19	500	19	450	18	18	356	11	11	69	64	30	225
5А 225 M	6; 8	820	967	535	550	140	140	311	149	65	60	19	500	19	450	18	18	356	11	11	69	64	30	225
5АИ 225 M	2	840	955	515	550	110		311	149	55		19	500	19	450	16		356	10		59		25	225
5АИ 225 M	4; 6; 8	870	1015	515	550	140		311	149	65		19	500	19	450	18		356	11		69		25	225
5АИ 250 S	2	910		610	550	140		311	168	65		24	500	19	450	18		406	11				32	250
5АИ 250 S	4; 6; 8	910		610	550	140		311	168	75		24	500	19	450	20		406	12				32	250
5А 250 S	2	930	1045	615	550	140	110	311	168	65	55	24	500	19	450	18	16	406	11	11	69	59	30	250
5А 250 S	4; 6; 8	930	1075	615	550	140	140	311	168	75	65	24	500	19	450	20	18	406	12	12	79,5	69	30	250
5АИ 250 M	2	910		610	550	140		349	168	65		24	500	19	450	18		406	11				32	250
5АИ 250 M	4; 6; 8	910		610	550	140		349	168	75		24	500	19	450	20		406	12				32	250
5А 250 M	2	930	1045	615	550	140	110	349	168	65	55	24	500	19	450	18	16	406	11	11	69	59	32	250
5А 250 M	4; 6; 8	930	1075	615	550	140	140	349	168	75	65	24	500	19	450	20	18	406	12	12	79,5	69	32	250
5АИ 280 S	2	1000		660	660	140		368	190	70		24	600	24	550	20		457	12				32	280
5АИ 280 S	4; 6; 8	1000		660	660	170		368	190	80		24	600	24	550	22		457	14				32	280
5А 280 S	2	1050	1165	645	660	140	140	368	190	70	65	24	600	24	550	20	18	457	12	12	74,5	69	30	280
5А 280 S	4; 6; 8; 10	1020	1135	645	660	170	140	368	190	80	65	24	600	24	550	22	18	457	14	14	85	69	30	280
5АИ 280 M	2	1080		660	660	140	140	419	190	70	65	24	600	24	550	20		457	12				30	280
5АИ 280 M	4; 6; 8	1110		660	660	170	140	419	190	80	65	24	600	24	550	22		457	14				30	280

Тип электро- двигателя	Число полюсов	Габаритные размеры, мм				Установочные и присоединительные размеры, мм																		
		L30	L33	h31	d24	L1	L2	L10	L31	d1	d2	d10	d20	d22	d25	b1	b2	b10	h1	h2	h5	h6	h10	h
5A 280 M	2	1050	1165	645	660	140	140	419	190	70	65	24	600	24	550	20	18	457	12	12	74,5	69	30	280
5A 280 M	4	1180	1285	735	660	170	140	419	190	80	65	24	600	24	550	22	18	457	14	14	85	69	30	280
5A 280 M	6; 8; 10	1140	1350	645	660	170	140	419	190	80	65	24	600	24	550	22	18	457	14	14	85	69	30	280
5AI 315 S	2	1330		865	660	140		406	216	75		28	600	24	550	20		508	12		79,5		44	315
5AI 315 S	4; 6; 8	1330		865	660	170		406	216	90		28	600	24	550	25		508	14		95		46	315
A 315 S	2	1230	1405	770	660	140	140	406	216	75	65	28	600	24	550	20	18	508	12	12	79,5	69,5	30	315
A 315 S	4; 6; 8; 10	1260	1435	770	660	170	140	406	216	90	65	28	600	24	550	25	18	508	14	14	95	69,5	30	315
5AI 315 M	2	1330		865	660	140		457	216	75		28	600	24	550	20		508	12		79,5		46	315
5AI 315 M	4; 6; 8; 10	1330		865	660	170		457	216	90		28	600	24	550	25		508	14		95		46	315
A 315 M	2	1230	1405	770	660	140	140	457	216	75	65	28	600	24	550	20	18	508	12	12	79,5	69,5	30	315
A 315 M	4	1330	1505	770	660	170	140	457	216	90	65	28	600	24	550	25	18	508	14	14	95	69,5	30	315
A 315 M	6; 8; 10	1260	1435	770	660	170	140	457	216	90	65	28	600	24	550	25	18	508	14	14	95	69,5	30	315
5AI 355 S	2	1565		1010	800	170		500	254	85		28	740	24	680	22	20	610	14	14	90	79,5	52	355
5AI 355 S	4; 6; 8; 10; 12	1565		1010	800	210		500	254	100		28	740	24	680	28	25	610	16	16	106	95	52	355
A 355 S	2	1475	1655	925	800	170	140	500	254	85	75	28	740	24	680	22	20	610	14	14	90	79,5	30	355
A 355 S	4; 6; 8; 10	1515	1725	925	800	210	170	500	254	100	90	28	740	24	680	28	25	610	16	16	106	95	30	355
5AI 355 M	2	1565		1010	800	170		560	254	85		28	740	24	680	22	20	610	14	14	90	79,5	52	355
5AI 355 M	4; 6; 8; 10; 12	1565		1010	800	210		560	254	100		28	740	24	680	28	25	610	16	16	106	95	52	355
A 355 M	2	1620	1800	925	800	170	140	560	254	85	75	28	740	24	680	22	20	610	14	14	90	79,5	30	355
A 355 M	4; 6; 8; 10	1660	1870	925	800	210	170	560	254	100	90	28	740	24	680	28	25	610	16	16	106	95	30	355

Габаритные, установочные и присоединительные размеры IM 2181/B34 и IM 3681/B14

Тип электро-двигателя	Число полюсов	Габаритные размеры, мм					Установочные и присоединительные размеры, мм																		
		l30	l33	d25	h31	l1	l2	l10	l20	l31	d1	d10	d20	d22	d24	b1	b10	h	h1	h5	h10				
5AI 56	2; 4	218	234	50	70	148	23	23	71	2,5	3,6	11	8,8	65	85	M6	M5	80	99	4	90	56	4	12,5	7
5AI 63	2; 4; 6	237	263	60	80	161	30	30	80	3,0	4,0	14	10	75	100	M6	M5	90	110	5	110	63	5	16	8
5AI 71	2; 4; 6; 8	272,5	316,5	70	95	188	40	40	90	3,0	4,5	19	10	85	115	M6	M8	105	140	6	112	71	6	21,5	8
5AI 80 A	2; 4; 6; 8	296,5	350	80	110	204,5	50	50	100	3,5	5,0	22	12	100	130	M6	M8	120	160	6	125	80	6	24,5	9
5AI 80 B	2; 4; 6; 8	320,5	374	80	110	204,5	50	50	100	3,5	5,0	22	12	100	130	M6	M8	120	160	6	125	80	6	24,5	9
5AI 90 L	2; 4; 6; 8	337	390	95	110	230	50	50	125	3,5	5,6	24	12	115	130	M8	M8	140	160	8	140	90	7	27	10
5AI 100 S	2; 4	360	424	110	110	246,5	60	60	112	3,5	6,3	28	16	130	130	M8	M8	160	160	8	160	100	7	31	12
5AI 100 L	2; 4; 6; 8	391	455	110	110	246,5	60	60	140	3,5	6,3	28	16	130	130	M8	M8	160	160	8	160	100	7	31	12

*В связи с постоянной работой по совершенствованию двигателей, в конструкцию могут быть внесены изменения, не отраженные в данном издании.