



Электродвигатели серии 5AM.
5AM-200, 5AM-250, IM 1001, IM 1002. Низковольтные.

Тип	l , мм	l_1 , мм	l_2 , мм	l_{33} , мм	l_{10} , мм	l_{11} , мм	l_{30} , мм	l_3 , мм	l_{31} , мм	b , мм	b_1 , мм	b_2 , мм	b_{10} , мм
5AM-200M-2	886	110	110	155	267	340	760	396	133	395	18	16	318
5AM-200L-2	892	110	110	155	267	340	780	446	133	395	16	16	318
5AM-200M-4	876	140	110	155	267	340	760	426	133	395	18	16	318
5AM-200L-4	922	140	110	155	305	390	810	476	133	395	18	16	318
5AM-200M-6	876	110	110	155	267	340	760	426	133	395	18	16	318
5AM-200L-6	922	110	110	155	305	390	810	476	133	395	18	16	318
5AM-200M-8	876	140	110	155	267	340	760	426	133	395	18	16	318
5AM-200L-8	922	140	110	155	305	390	810	476	133	395	18	16	318
5AM-225M-2	895	110	110	220	286	366	785	420	149	436	18	18	356
5AM-225M-4	935	140	140	220	286	366	815	420	149	436	18	18	356
5AM-225M-6	935	140	140	220	286	366	815	420	149	436	18	18	356
5AM-225M-8	935	140	140	220	286	366	815	420	149	436	18	18	356
5AM-250S-2	1035	140	140	225	311	390	895	371	168	490	20	18	406
5AM-250M-2	1075	140	140	225	349	430	935	391	168	490	20	18	406
5AM-250S-4	1035	140	140	225	311	390	895	371	168	490	20	18	406
5AM-250M-4	1075	140	140	225	349	430	935	391	168	490	20	18	406
5AM-250S-6	1035	140	140	225	311	390	895	371	168	490	20	18	406
5AM-250M-6	1075	140	140	225	349	430	935	391	168	490	20	18	406
5AM-250S-8	1035	140	140	225	311	390	895	371	168	490	20	18	406
5AM-250M-8	1075	140	140	225	349	430	930	391	168	490	20	18	406
5AM-250S-10	1035	140	140	225	311	390	895	371	168	490	20	18	406
Тип	b_{20} , мм	b_{30} , мм	h , мм	h_1 , мм	h_2 , мм	h_5 , мм	h_6 , мм	h_{31} , мм	h_{34} , мм	d_1 , мм	d_2 , мм	d_{10} , мм	-
5AM-200M-2	165	410	200	10	10	59	59	525	465	55	55	19	-
5AM-200L-2	165	410	200	10	10	59	59	525	465	55	55	19	-
5AM-200M-4	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-200L-4	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-200M-6	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-200L-6	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-200M-8	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-200L-8	165	410	200	11	10	59	59	525	465	60	55	19	-
5AM-225M-2	230	456	225	10	-	64	64	570	450	65	65	19	-
5AM-225M-4	230	456	225	11	-	64	64	570	450	65	65	19	-
5AM-225M-6	230	456	225	11	-	64	64	570	450	65	65	19	-
5AM-225M-8	230	456	225	11	-	64	64	570	450	65	65	19	-
5AM-250S-2	-	545	250	7,5	-	82,5	-	615	557,5	75	-	24	-
5AM-250M-2	-	545	250	7,5	-	82,5	-	615	558	75	-	24	-
5AM-250S-4	-	545	250	7,5	-	82,5	-	615	558	75	-	24	-
5AM-250M-4	-	545	250	7,5	-	82,5	-	615	557,5	75	-	24	-
5AM-250S-6	-	545	250	7,5	-	82,5	-	615	557,5	75	-	24	-
5AM-250M-6	-	545	250	7,5	-	82,5	-	615	558	75	-	24	-
5AM-250S-8	-	545	250	7,5	-	82,5	-	615	558	75	-	24	-
5AM-250M-8	-	545	250	7,5	-	82,5	-	615	558	75	-	24	-
5AM-250S-10	-	545	250	7,5	-	82,5	-	615	557,5	75	-	24	-